

The server part, controlling the launch of the application, is available for Linux as a binary and as source code for Unix Systems, not supported by the standard binary.

A Sound Channel is provided for streaming audio from an application running on the server.

:: CXC™/X900™ OEM Opportunity

OEMs can license our SmartFLeX Client OS to build their own brand-name SmartClient on their own hardware or our hardware base.

VARs and System Integrators can license a customized total solution to brand their own SmartClient version for their vertical solution.

CXC and **X900**, developed by SmartFLeX Technology – the leader in Linux based Thin Client Technology, are the most flexible and unique Network Client solution for sophisticated, end user friendly Office, Retail and general Information and Computing Applications in dedicated Unix and Linux environments.

SmartFLeX Technology reserves the right to change technical specifications without notice.

Trademarks:
CXC, X900, NETION, EPSION, OPTION, DATIX, APPLIX, SmartClient, SmartServer and CSM are SmartFLeX Technology registered or unregistered Trademarks.
Linux is a Trademark of Linux Torvalds and HP JetDirect is a Trademark of Hewlett Packard Corporation.
NX, ICA, RDP, VNC, Mozilla are trademarks of their respective owners.

:: CXC™/X900™ Features

Firmware:

- Linux Kernel

Client Options:

- Character-based Terminal Mode (CXC)
- X-Terminal Mode via REXEC and XDMCP
- Emulator Suite (for CXC only)
- Client up detection (X900 only)
- Optimized for port redirection
- Available port server daemon for Linux

Printing:

- lpd/rsh/HP JetDirect printing
- Printing support via parallel, serial or USB

Hardware:

- Processor: 800 MHz (fanless) or 533 MHz (w or w/o fan, special order)
- Memory: 128 MB (upgradable)
- Flash Module: 32 MB
- Video: Embedded, shared video memory 1280 x 1024 pixel max. 24 Bit color
- Network Interface: 10/100 Mbit/s
- 2 COM Ports
- One LPT Port
- 1 VGA port
- 1 PS/2 mouse port
- 1 PS/2 keyboard port
- 2 x USB (/A), 3 x USB or 4 x USB (/S)
- Build-in Sound
- AC outsensing, Ext. PS (A), int. PS (/S)
- Case: black/silver (/A), black (/S)
- Also available as a 733 Mhz integrated unit with 17" LCD Flat Screen, ideal for POS, Hospitals and Hospitality applications.



SmartClients™

(Network Terminals)

CXC™

X900™



SmartFLeX Technology, Inc.
31 Stonecroft Dr., Suite 105
Easton, PA 18045-2812, USA
Phone: +1 (610) 849-0196
Fax: +1 (610) 849-0197

www.smartflectech.com

